

w.c.s. - Bug #13917

Erreur lors de l'import d'un wf

09 novembre 2016 15:18 - Josué Kouka

| | | | |
|------------------------|--------|----------------------|------------------|
| Statut: | Fermé | Début: | 09 novembre 2016 |
| Priorité: | Normal | Echéance: | |
| Assigné à: | | % réalisé: | 0% |
| Catégorie: | | Temps estimé: | 0:00 heure |
| Version cible: | v1.65 | Planning: | |
| Patch proposed: | Oui | | |

Description

Exception:

```
type = '<type 'exceptions.AttributeError'>', value = ''NoneType' object has no attribute 'fields'
''
```

Stack trace (most recent call first):

```
File "/usr/lib/python2.7/dist-packages/wcs/workflows.py", line 239, in __init__
  237      self.workflow = workflow
  238      if workflow.variables_formdef and workflow.variables_formdef.fields:
> 239          self.fields = self.workflow.variables_formdef.fields
  240          self.max_field_id = max([lax_int(x.id) for x in self.fields or []])
  241      else:
```

locals:

```
self = <WorkflowVariablesFieldsFormDef 'Nancy en Direct' id:None>
workflow = <Workflow 'Nancy en Direct' id:None>
```

```
File "/usr/lib/python2.7/dist-packages/wcs/workflows.py", line 606, in import_from_xml_tree
  604      formdef = variables.find('formdef')
  605      imported_formdef = FormDef.import_from_xml_tree(formdef, include_id=True)
> 606      workflow.backoffice_fields_formdef = WorkflowVariablesFieldsFormDef(workflow=wo
rkflow)
  607      workflow.backoffice_fields_formdef.fields = imported_formdef.fields
  608
```

locals:

```
status_o = <wcs.workflows.WorkflowStatus object at 0x7f0426763dd0>
status = <Element 'status' at 0x3502e50>
level_o = <wcs.workflows.WorkflowCriticalityLevel object at 0x7f041e91f3d0>
node = <Element 'last_modification' at 0x7f0424af8e90>
level = <Element 'criticality-level' at 0x50bb550>
formdef = <Element 'formdef' at 0x47484d0>
variables = <Element 'backoffice-fields' at 0x4748190>
workflow = <Workflow 'Nancy en Direct' id:None>
tree = <Element 'workflow' at 0x3d8b450>
role_node = <Element 'role' at 0x7f0424af8e50>
global_actions = <Element 'global_actions' at 0x3502310>
action_o = <wcs.workflows.WorkflowGlobalAction object at 0x7f042533e150>
include_id = False
action = <Element 'action' at 0x7f042563e4d0>
cls = <class 'wcs.workflows.Workflow'>
charset = 'utf-8'
imported_formdef = <FormDef '-' id:None>
criticality_levels = <Element 'criticality_levels' at 0x50bbf90>
```

```
File "/usr/lib/python2.7/dist-packages/wcs/workflows.py", line 538, in import_from_xml
  536      except:
  537          raise ValueError()
> 538      return cls.import_from_xml_tree(tree, include_id=include_id)
  539
  540 @classmethod
```

```

locals:
fd = <open file '<fdopen>', mode 'w+b' at 0x7f042590af60>
tree = <xml.etree.ElementTree.ElementTree object at 0x7f042463ac10>
include_id = False
cls = <class 'wcs.workflows.Workflow'>

File "/usr/lib/python2.7/dist-packages/wcs/admin/workflows.py", line 1894, in import_submit
1892     reason = _(e)
1893     except ValueError:
> 1894         error = True
1895
1896     if error:

locals:
fp = <open file '<fdopen>', mode 'w+b' at 0x7f042590af60>
reason = None
self = <wcs.admin.workflows.WorkflowsDirectory object at 0x23e2550>
form = <wcs.qcommon.form.Form object at 0xa471450>
error = False

File "/usr/lib/python2.7/dist-packages/wcs/admin/workflows.py", line 1857, in p_import
1855     return self.import_submit(form)
1856     except ValueError:
> 1857         pass
1858
1859     get_response().breadcrumb.append( ('workflows/', _('Workflows')) )

locals:
self = <wcs.admin.workflows.WorkflowsDirectory object at 0x23e2550>
form = <wcs.qcommon.form.Form object at 0xa471450>

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 67, in _q_traverse
65     raise TraversalError
66     elif hasattr(obj, '__call__'):
> 67         return obj()
68     else:
69         return obj

locals:
component = 'import'
self = <wcs.admin.workflows.WorkflowsDirectory object at 0x23e2550>
obj = <bound method WorkflowsDirectory.p_import of <wcs.admin.workflows.WorkflowsDirectory object at 0x23e2550>>
name = 'p_import'
path = []

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 63, in _q_traverse
61     if path:
62         if hasattr(obj, '_q_traverse'):
> 63             return obj._q_traverse(path)
64         else:
65             raise TraversalError

locals:
component = 'workflows'
self = <modules.backoffice.BackofficeRootDirectory object at 0x337c710>
obj = <wcs.admin.workflows.WorkflowsDirectory object at 0x23e2550>
name = None
path = ['import']

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 91, in _q_traverse
89     def _q_traverse(self, path):
90         self._q_access()
> 91         return super(AccessControlled, self)._q_traverse(path)
92
93

```

```

locals:
path = ['workflows', 'import']
self = <modules.backoffice.BackofficeRootDirectory object at 0x337c710>

File "/usr/lib/python2.7/dist-packages/wcs/backoffice/root.py", line 78, in __traverse
  76         pass
  77     get_response().add_javascript(['jquery.js', 'qcommon.js', 'gadjo.js'])
>  78     return super(RootDirectory, self).__traverse(path)
  79
  80 @classmethod

locals:
path = ['workflows', 'import']
self = <modules.backoffice.BackofficeRootDirectory object at 0x337c710>

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 63, in __traverse
  61     if path:
  62         if hasattr(obj, '__traverse__'):
>  63             return obj.__traverse__(path)
  64         else:
  65             raise TraversalError

locals:
component = 'backoffice'
self = <modules.rootAlternateRootDirectory object at 0x2f76590>
obj = <modules.backoffice.BackofficeRootDirectory object at 0x337c710>
name = 'backoffice'
path = ['workflows', 'import']

File "/usr/lib/pymodules/python2.7/extrawcsauquotidien/modules/root.py", line 844, in __traverse
  842             return redirect('%s%s/%s' % (base_url, f.category.url_name, uri_rest))
  843
>  844             raise e
  845
  846

locals:
path = ['backoffice', 'workflows', 'import']
self = <modules.rootAlternateRootDirectory object at 0x2f76590>
response = <qcommon.http_response.HTTPResponse instance at 0x81284d0>

File "/usr/lib/pymodules/python2.7/quixote/publish.py", line 253, in try_publish
  251             permanent=True)
  252         components = path[1:].split('/')
>  253         output = self.root_directory.__traverse__(components)
  254         # The callable ran OK, commit any changes to the session
  255         self.finish_successful_request()

locals:
path = '/backoffice/workflows/import'
self = <publisher.WcsPublisher object at 0x2f765d0>
request = <qcommon.http_request.HTTPRequest instance at 0x8128e18>
components = ['backoffice', 'workflows', 'import']

File "/usr/lib/python2.7/dist-packages/wcs/qcommon/publisher.py", line 623, in try_publish
  621     for extra_source in self.extra_sources:
  622         self.substitutions.feed(extra_source(self, request))
>  623     return Publisher.try_publish(self, request)
  624
  625 def get_site_language(self):

locals:
extra_source = <class 'modules.abelium_domino_vars.DominoVariables'>
pystatsd = <module 'qcommon.vendor.pystatsd' from '/usr/lib/python2.7/dist-packages/wcs/qcommon/vendor/pystatsd.py'>
request = <qcommon.http_request.HTTPRequest instance at 0x8128e18>
```

```

script_name = ''
prefix = 'm'
override_template_keys = {'m': 'mobile'}
canonical_hostname = 'demarches.nancy.fr'
self = <publisher.WcsPublisher object at 0x2f765d0>

File "/usr/lib/python2.7/dist-packages/wcs/publisher.py", line 227, in try_publish
  225      if request.get_header('X_WCS_IFRAME_MODE', '') in ('true', 'yes'):
  226          request.responseiframe_mode = True
> 227      return QommonPublisher.try_publish(self, request)
  228
  229  def get_object_visitors(self, object_key):

locals:
    self = <publisher.WcsPublisher object at 0x2f765d0>
    request = <qommon.http_request.HTTPRequest instance at 0x8128e18>

File "/usr/lib/pymodules/python2.7/quixote/publish.py", line 281, in process_request
  279      except:
  280          # Some other exception, generate error messages to the logs, etc.
> 281          output = self.finish_failed_request()
  282          output = self.filter_output(request, output)
  283          self.logger.log_request(request, start_time)

locals:
    start_time = 1478700919.84975
    request = <qommon.http_request.HTTPRequest instance at 0x8128e18>
    self = <publisher.WcsPublisher object at 0x2f765d0>

File "/usr/lib/python2.7/dist-packages/wcs/qommon/publisher.py", line 932, in process
  930      def process(self, stdin, env):
  931          request = HTTPRequest(stdin, env)
> 932          self.response = self.process_request(request)
  933          return self.response
  934

locals:
    self = <publisher.WcsPublisher object at 0x2f765d0>
    stdin = <open file '<socket>', mode 'r' at 0x31508a0>
    request = <qommon.http_request.HTTPRequest instance at 0x8128e18>
    env = {'HTTP_REFERER': 'https://demarches.nancy.fr/backoffice/workflows/', 'SCRIPT_NAME': '',
'REQUEST_METHOD': 'POST', 'PATH_INFO': '/backoffice/workflows/import', 'SERVER_PROTOCOL': 'HTTP/1.1', 'QUERY_STRING': '', 'CONTENT_LENGTH': '31390', 'HTTP_USER_AGENT': 'Mozilla/5.0 (X11; Linux x86_64; rv:45.0) Gecko/20100101 Firefox/45.0', 'HTTP_CONNECTION': 'keep-alive', 'HTTP_COOKIE': 'publik_portal_agent_url=https%3A%2F%2Fportail-agent.nancy.fr%2F; publik_portal_agent_title=Portail%20agent; wcs-257271="8f097cc7db958e8b"; A2_OPENED_SESSION=1', 'SERVER_NAME': 'demarches.nancy.fr', 'REMOTE_ADDR': '80.12.92.47', 'SERVER_PORT': '443', 'DOCUMENT_ROOT': '/etc/nginx/html', 'CONTENT_TYPE': 'multipart/form-data; boundary=-----1160534339443424881772538709', 'DOCUMENT_URI': '/backoffice/workflows/import', 'REMOTE_USER': '2', 'HTTP_HOST': 'demarches.nancy.fr', 'HTTPS': 'yes', 'HTTP_CONTENT_TYPE': 'multipart/form-data; boundary=-----1160534339443424881772538709', 'HTTP_CONTENT_LENGTH': '31390', 'REQUEST_URI': '/backoffice/workflows/import', 'HTTP_ACCEPT': 'text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8', 'REMOTE_PORT': '59420', 'HTTP_ACCEPT_LANGUAGE': 'en-US,en;q=0.5', 'SCGI': '1', 'HTTP_ACCEPT_ENCODING': 'gzip, deflate'}

File "/usr/lib/pymodules/python2.7/quixote/server/scgi_server.py", line 27, in handle_connection
  25      env['PATH_INFO'] = path[len(prefix):] + env.get('PATH_INFO', '')
  26
> 27      response = self.publisher.process(input, env)
  28      try:
  29          response.write(output)

locals:
    output = <open file '<socket>', mode 'w' at 0x47bec90>
    self = <qommon.scgi_server.QommonHandler instance at 0x32875f0>
    conn = <socket object, fd=46, family=2, type=1, protocol=0>
    env = {'HTTP_REFERER': 'https://demarches.nancy.fr/backoffice/workflows/', 'SCRIPT_NAME': ''}

```

```

'REQUEST_METHOD': 'POST', 'PATH_INFO': '/backoffice/workflows/import', 'SERVER_PROTOCOL': 'HTTP/1
.1', 'QUERY_STRING': '', 'CONTENT_LENGTH': '31390', 'HTTP_USER_AGENT': 'Mozilla/5.0 (X11; Linux x8
6_64; rv:45.0) Gecko/20100101 Firefox/45.0', 'HTTP_CONNECTION': 'keep-alive', 'HTTP_COOKIE': 'publ
ik_portal_agent_url=https%3A%2F%2Fportail-agent.nancy.fr%2F; publik_portal_agent_title=Portail%20a
gent; wcs-257271="8f097cc7db958e8b"; A2_OPENED_SESSION=1', 'SERVER_NAME': 'demarches.nancy.fr', 'R
EMOTE_ADDR': '80.12.92.47', 'SERVER_PORT': '443', 'DOCUMENT_ROOT': '/etc/nginx/html', 'CONTENT_TYP
E': 'multipart/form-data; boundary=-----1160534339443424881772538709', 'DOCU
MENT_URI': '/backoffice/workflows/import', 'REMOTE_USER': '2', 'HTTP_HOST': 'demarches.nancy.fr',
'HTTPS': 'yes', 'HTTP_CONTENT_TYPE': 'multipart/form-data; boundary=-----116
053433944342488177
2538709', 'HTTP_CONTENT_LENGTH': '31390', 'REQUEST_URI': '/backoffice/workflows/import', 'HTTP_AC
CEPT': 'text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8', 'REMOTE_PORT': '59420',
'HTTP_ACCEPT_LANGUAGE': 'en-US,en;q=0.5', 'SCGI': '1', 'HTTP_ACCEPT_ENCODING': 'gzip, deflate'}
    input = <open file '<socket>', mode 'r' at 0x31508a0>

File "/usr/lib/python2.7/dist-packages/wcs/qommon/scgi_server.py", line 35, in handle_connection
  33     def handle_connection(self, conn):
  34         self.number_of_connection_handled = self.number_of_connection_handled + 1
>  35     quixote.server.scgi_server.QuixoteHandler.handle_connection(self, conn)
  36     # input, output and conn are closed, long running jobs could be done
  37     # here.

locals:
  self = <qommon.scgi_server.QommonHandler instance at 0x32875f0>
  conn = <socket object, fd=46, family=2, type=1, protocol=0>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 71, in serve
  69         conn.setblocking(1)
  70         os.close(fd)
>  71     self.handle_connection(conn)
  72
  73

locals:
  self = <qommon.scgi_server.QommonHandler instance at 0x32875f0>
  fd = 45
  conn = <socket object, fd=46, family=2, type=1, protocol=0>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 194, in spawn_child
  192         # the connection in the child
  193         os.close(child_fd)
>  194     self.handler_class(parent_fd).serve()
  195     sys.exit(0)
  196 else:

locals:
  self = <qommon.scgi_server.SCGIServer instance at 0x2eae7e8>
  pid = 0
  flags = 2
  child_fd = 33
  parent_fd = 32
  conn = <socket._socketobject object at 0x2fb0830>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 308, in delegate_request
  306         # start more children if we haven't met max_children limit
  307         if len(self.children) < self.max_children:
>  308             self.spawn_child(conn)
  309
  310         # Start blocking inside select. We might have reached

locals:
  e = []
  w = []
  self = <qommon.scgi_server.SCGIServer instance at 0x2eae7e8>
  r = [33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44]
  timeout = 0
  child_fd = 33

```

```

ready_byte = ''
conn = <socket._socketobject object at 0x2fb0830>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 327, in serve_on_socket
  325         try:
  326             conn, addr = self.socket.accept()
  > 327             self.delegate_request(conn)
  328             conn.close()
  329         except socket.error, e:

locals:
    s = <socket._socketobject object at 0x2fb0750>
    addr = ('127.0.0.1', 40597)
    conn = <socket._socketobject object at 0x2fb0830>
    self = <qcommon.scgi_server.SCGIServer instance at 0x2eae7e8>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 336, in serve
  334
  335     def serve(self):
  > 336         self.serve_on_socket(self.get_listening_socket())
  337
  338

locals:
    self = <qcommon.scgi_server.SCGIServer instance at 0x2eae7e8>

File "/usr/lib/python2.7/dist-packages/wcs/qcommon/scgi_server.py", line 74, in run
  72     s = SCGIServer(create_handler, host=host, port=port,
  73                     max_children=max_children)
  > 74     s.serve()
  75
  76

locals:
    create_handler = <function create_handler at 0x27e2848>
    handler_connection_limit = -1
    max_children = 16
    create_publisher = <bound method type.create_publisher of <class 'publisher.WcsPublisher'>>
    host = 'localhost'
    script_name = None
    s = <qcommon.scgi_server.SCGIServer instance at 0x2eae7e8>
    spawn_cron = True
    port = 3001

File "/usr/lib/python2.7/dist-packages/wcs/ctl/start.py", line 138, in execute
  136
  137     try:
  > 138         run_function(publisher.WcsPublisher.create_publisher, **run_kwargs)
  139     except socket.error, e:
  140         self.del_pid()

locals:
    publisher = <module 'publisher' from '/usr/lib/python2.7/dist-packages/wcs/publisher.pyc'>
    base_app_dir = '/var/lib/wcs-au-quotidien'
    args = []
    tenant_path = '/var/lib/wcs-au-quotidien/demarches.alfortville.fr'
    self = <wcs.ctl.start.CmdStart object at 0x1d0b790>
    hostname = 'demarches.alfortville.fr'
    pub = <publisher.WcsPublisher object at 0x32a0750>
    sub_options = <Values at 0x1d57638: {'http': False, 'silent': False, 'app_dir': None, 'extra': ['/usr/lib/pymodules/python2.7/extrawcs-au-quotidien/'], 'max_children': None, 'handler_connection_limit': None, 'script_name': None, 'daemonize': False, 'data_dir': None, 'port': 3001, 'pidfile': None}>
    run_function = <function run at 0x1d2a500>
    base_options = <Values at 0x1d0f1b8: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>
    run_kwargs = {'max_children': 16, 'port': 3001, 'spawn_cron': True}

```

```

File "/usr/lib/python2.7/dist-packages/wcs/qommon/ctl.py", line 69, in run
    67         for i, extra in enumerate(sub_options.extra):
    68             self.config.set("extra", "cmd_line_extra_%d" % i, extra)
>   69     return self.execute(base_options, sub_options, args)
    70
    71 def parse_args(self, args):

locals:
extra = '/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/'
i = 0
self = <wcs.ctl.start.CmdStart object at 0x1d0b790>
args = []
sub_options = <Values at 0x1d57638: {'http': False, 'silent': False, 'app_dir': None, 'extra': ['/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/'], 'max_children': None, 'handler_connect': None, 'connection_limit': None, 'script_name': None, 'daemonize': False, 'data_dir': None, 'port': 3001, 'pidfile': None}>
base_options = <Values at 0x1d0f1b8: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>

File "/usr/lib/python2.7/dist-packages/wcs/qommon/ctl.py", line 159, in run
    157     command_class = self.get_commands()[command]
    158     cmd = command_class()
>   159     return cmd.run(args, options)
    160

locals:
cmd = <wcs.ctl.start.CmdStart object at 0x1d0b790>
args = ['--extra', '/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/']
self = <wcs.qommon.ctl.Ctl object at 0x193f3d0>
command_class = <class 'wcs.ctl.start.CmdStart'>
command = 'start'
cmd_prefix = 'wcs.ctl'
options = <Values at 0x1d0f1b8: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>

File "/usr/sbin/wcsctl", line 8, in <module>
    6
    7 ctl = wcs.qommon.ctl.Ctl(cmd_prefixes=['wcs.ctl'])
>   8 ctl.run(sys.argv[1:])
    9

locals:
wcs = <module 'wcs' from '/usr/lib/python2.7/dist-packages/wcs/__init__.pyc'>
__builtins__ = <module '__builtin__' (built-in)>
__file__ = '/usr/sbin/wcsctl'
__package__ = None
sys = <module 'sys' (built-in)>
ctl = <wcs.qommon.ctl.Ctl object at 0x193f3d0>
__name__ = '__main__'
__doc__ = None

Form:
_form_id      'b98f9f8e220d9340'
file          <Upload at 8128ea8: nancy-en-direct.wcs>
submit        'Importer le workflow'
url           ''

Cookies:
A2_OPENED_SESSION '1'
publik_portal_agent_title 'Portail%20agent'
publik_portal_agent_url 'https%3A%2F%2Fportail-agent.nancy.fr%2F'
wcs-257271      '8f097cc7db958e8b'

Environment:
CONTENT_LENGTH  '31390'
CONTENT_TYPE     'multipart/form-data; boundary=-----116053433944342488177253
8709'
DOCUMENT_ROOT    '/etc/nginx/html'
DOCUMENT_URI     '/backoffice/workflows/import'

```

```

HTTPS           'yes'
HTTP_ACCEPT    'text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8'
HTTP_ACCEPT_ENCODING 'gzip, deflate'
HTTP_ACCEPT_LANGUAGE 'en-US,en;q=0.5'
HTTP_CONNECTION 'keep-alive'
HTTP_CONTENT_LENGTH '31390'
HTTP_CONTENT_TYPE 'multipart/form-data; boundary=-----1160534339443424881772
538709'
HTTP_COOKIE     'publik_portal_agent_url=https%3A%2F%2Fportail-agent.nancy.fr%2F; publik_portal_ag
ent_title=Portail%20agent; wcs-257271="8f097cc7db958e8b"; A2_OPENED_SESSION=1'
HTTP_HOST       'demarches.nancy.fr'
HTTP_REFERER    'https://demarches.nancy.fr/backoffice/workflows/'
HTTP_USER_AGENT 'Mozilla/5.0 (X11; Linux x86_64; rv:45.0) Gecko/20100101 Firefox/45.0'
PATH_INFO       '/backoffice/workflows/import'
QUERY_STRING    ''
REMOTE_ADDR    '80.12.92.47'
REMOTE_PORT    '59420'
REMOTE_USER    '2'
REQUEST_METHOD 'POST'
REQUEST_URI    '/backoffice/workflows/import'
SCGI           '1'
SCRIPT_NAME    ''
SERVER_NAME    'demarches.nancy.fr'
SERVER_PORT    '443'
SERVER_PROTOCOL 'HTTP/1.1'

```

Révisions associées

Révision 7b640d0d - 09 novembre 2016 15:56 - Frédéric Péters

formdefs: allow setting a workflow being imported (#13917)

When a workflow is being imported it doesn't have an id and couldn't therefore be attached to a formdef; however there are internal workflow formdefs (for the workflow variables) and they need to be associated to the being-imported workflow.

Historique

#1 - 09 novembre 2016 15:25 - Josué Kouka

- Fichier *nancy-en-direct.wcs* ajouté

#2 - 09 novembre 2016 15:31 - Frédéric Péters

- Fichier *0001-formdefs-allow-setting-a-workflow-being-imported-139.patch* ajouté
- Statut changé de Nouveau à En cours
- Patch proposed changé de Non à Oui

#3 - 09 novembre 2016 15:36 - Thomas Noël

Ack

#4 - 09 novembre 2016 15:56 - Frédéric Péters

- Statut changé de En cours à Résolu (à déployer)

```

commit 7b640d0dd8f63774a8ac636a4ede3ff3759cabdf
Author: Frédéric Péters <fpeters@entrouvert.com>
Date:   Wed Nov 9 15:24:48 2016 +0100

```

formdefs: allow setting a workflow being imported (#13917)

When a workflow is being imported it doesn't have an id and couldn't therefore be attached to a formdef; however there are internal workflow formdefs (for the workflow variables) and they need to be associated to the being-imported workflow.

#5 - 04 décembre 2016 13:05 - Frédéric Péters

- Version cible mis à v1.65

- Statut changé de Résolu (à déployer) à Fermé

Fichiers

| | | |
|---|------------------------------|-----------------|
| nancy-en-direct.wcs | 30,1 ko 09 novembre 2016 | Josué Kouka |
| 0001-formdefs-allow-setting-a-workflow-being-imported-139.patch | 1008 octets 09 novembre 2016 | Frédéric Péters |