

w.c.s. - Bug #50502

erreur "maximum recursion depth exceeded in comparison" lors de l'accès à une vue de fiche personnalisée

25 janvier 2021 11:51 - Serghei Mihai

Statut:	Fermé	Début:	25 janvier 2021
Priorité:	Normal	Echéance:	
Assigné à:		% réalisé:	0%
Catégorie:		Temps estimé:	0:00 heure
Version cible:		Planning:	Non
Patch proposed:	Non		

Description

Pas sûr des conditions dans lesquelles cela arrive:

Exception:

```
type = '<class 'RecursionError'>', value = 'maximum recursion depth exceeded in comparison'
```

Stack trace (most recent call first):

```
File "/usr/lib/python3.7/gettext.py", line 453, in gettext
 451     def gettext(self, message):
 452         missing = object()
> 453         tmsg = self._catalog.get(message, missing)
 454         if tmsg is missing:
 455             if self._fallback:
```

locals:

```
message = 'Recipient'
missing = <object object at 0x7f4ccafe15d0>
self = <DjangoTranslation lang:fr>
```

File "/usr/lib/python3/dist-packages/django/utils/translation/trans_real.py", line 324, in do_translate

```
322         translation_object = getattr(_active, "value", _default)
323
> 324         result = getattr(translation_object, translation_function)(eol_message)
325
326     if isinstance(message, SafeData):
```

locals:

```
eol_message = 'Recipient'
message = 'Recipient'
translation_function = 'gettext'
translation_object = <DjangoTranslation lang:fr>
```

File "/usr/lib/python3/dist-packages/django/utils/translation/trans_real.py", line 338, in gettext

```
336     Returns a string on Python 3 and an UTF-8-encoded bytestring on Python 2.
337     """
> 338     return do_translate(message, 'gettext')
339
340
```

locals:

```
message = 'Recipient'
```

File "/usr/lib/python3/dist-packages/django/utils/translation/__init__.py", line 81, in gettext

```
79
80 def gettext(message):
> 81     return _trans.gettext(message)
82
```

83

```
locals:  
  message = 'Recipient'
```

```
File "/usr/lib/python3/dist-packages/wcs/qommon/__init__.py", line 46, in _  
  44     if pub is None:  
  45         return message  
> 46     return force_str(force_text(pub.gettext(str(message))))  
  47  
  48
```

```
locals:  
  message = 'Recipient'  
  pub = <wcs.compat.CompatWcsPublisher object at 0x7f4ccaa2f898>
```

```
File "/usr/lib/python3/dist-packages/wcs/workflows.py", line 350, in __init__  
  348     self.name = name  
  349     self.possible_status = []  
> 350     self.roles = {'_receiver': _('Recipient')}  
  351     self.global_actions = []  
  352     self.criticality_levels = []
```

```
locals:  
  name = 'Par défaut (fiches)'  
  self = <Workflow 'Par défaut (fiches)' id:None>
```

```
File "/usr/lib/python3/dist-packages/wcs/carddef.py", line 90, in get_default_workflow  
  88         ChoiceWorkflowStatusItem, Workflow)  
  89     from wcs.wf.remove import RemoveWorkflowStatusItem  
> 90     workflow = Workflow(name=_('Default (cards)'))  
  91     workflow.id = '_carddef_default'  
  92     workflow.roles = {
```

```
locals:  
  ChoiceWorkflowStatusItem = <class 'wcs.workflows.ChoiceWorkflowStatusItem'>  
  EditableWorkflowStatusItem = <class 'wcs.workflows.EditableWorkflowStatusItem'>  
  RemoveWorkflowStatusItem = <class 'wcs.wf.remove.RemoveWorkflowStatusItem'>  
  Workflow = <class 'wcs.workflows.Workflow'>  
  cls = <class 'wcs.carddef.CardDef'>
```

```
File "/usr/lib/python3/dist-packages/wcs/formdef.py", line 440, in get_workflow  
  438     return self._workflow  
  439     else:  
> 440     return self.get_default_workflow()  
  441  
  442     @classmethod
```

```
locals:  
  Workflow = <class 'wcs.workflows.Workflow'>  
  self = <CardDef 'Renseignements - démarche - catégorie - objet - services traitants' id:3>
```

```
File "/usr/lib/python3/dist-packages/wcs/formdef.py", line 397, in get_all_fields  
  395  
  396     def get_all_fields(self):  
> 397     return (self.fields or []) + self.workflow.get_backoffice_fields()  
  398  
  399     def get_widget_fields(self):
```

```
locals:  
  self = <CardDef 'Renseignements - démarche - catégorie - objet - services traitants' id:3>
```

```
File "/usr/lib/python3/dist-packages/wcs/backoffice/management.py", line 1637, in get_formdef_fields  
  1635         yield UserRelatedField(field)  
  1636  
> 1637     for field in self.formdef.get_all_fields():
```

```
1638         yield field
1639         if not get_publisher().is_using_postgresql():

locals:
  field = <StringField _avatar 'Avatar'>
  self = <wcs.backoffice.data_management.CardPage object at 0x7f4cc87f3320>

...
Environment:
HTTP_ACCEPT          'text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8'
HTTP_ACCEPT_ENCODING 'gzip, deflate, br'
HTTP_ACCEPT_LANGUAGE 'fr,fr-FR;q=0.8,en-US;q=0.5,en;q=0.3'
HTTP_CONNECTION      'close'
HTTP_HOST             'services-test.demarches.grenoblealpesmetropole.fr'
HTTP_REFERER          'https://services-test.demarches.grenoblealpesmetropole.fr/backoffice/data/demarche-categorie-objet-service-traitant/liste-des-demarches-thematiques/'
HTTP_UPGRADE_INSECURE_REQUESTS '1'
HTTP_USER_AGENT       'Mozilla/5.0 (Windows NT 10.0; WOW64; rv:68.0) Gecko/20100101 Firefox/68.0'
HTTP_X_FORWARDED_HOST 'services-test.demarches.grenoblealpesmetropole.fr'
HTTP_X_FORWARDED_PROTO 'https'
HTTP_X_FORWARDED_PROTOCOL 'ssl'
HTTP_X_FORWARDED_SERVER 'test.demarches.grenoblealpesmetropole.fr'
HTTP_X_FORWARDED_SSL 'on'
PATH_INFO             '/backoffice/data/demarche-categorie-objet-service-traitant/pardefaut/'
QUERY_STRING          ''
REQUEST_METHOD        'GET'
REQUEST_URI           '/backoffice/data/demarche-categorie-objet-service-traitant/pardefaut/'

A priori il y a eu des suppressions de champs dans le modèle de fiche après la construction de vues personnalisées.
```

Historique

#2 - 03 décembre 2023 20:15 - Frédéric Péters

- Statut changé de Nouveau à Fermé

Pas sûr des conditions dans lesquelles cela arrive:

Pas l'impression d'avoir revu ça, si jamais ça arrive, espérons que les conditions soient plus claires.