

## perte des infos saisies lors du recap

04 novembre 2015 21:46 - Thomas Noël

<b>Statut:</b>	Fermé	<b>Début:</b>	04 novembre 2015
<b>Priorité:</b>	Haut	<b>Echéance:</b>	
<b>Assigné à:</b>		<b>% réalisé:</b>	0%
<b>Catégorie:</b>		<b>Temps estimé:</b>	0:00 heure
<b>Version cible:</b>		<b>Planning:</b>	
<b>Patch proposed:</b>	Non		

**Description**

Sur <https://demarches-alfortville.test.entrouvert.org/famille/creation-de-votre-profil-famille/> : la saisie se passe bien, mais sur le récap final, tout est vide, et lorsqu'on valide, trace :

```
Exception:
  type = '<type 'exceptions.AssertionError'>', value = ''

Stack trace (most recent call first):
  File "/usr/lib/python2.7/dist-packages/wcs/sql.py", line 825, in get_sql_dict_from_data
    823         assert isinstance(value, basestring)
    824         elif sql_type == 'date':
> 825         assert type(value) is time.struct_time
    826         value = datetime.datetime(value.tm_year, value.tm_mon, value.tm_mday)
    827         elif sql_type == 'bytea':

locals:
  sql_type = 'date'
  sql_dict = {'f4': '', 'f176': None, 'f96': 'Oui', 'f176_structured': bytearray(b'N.'), 'f105': '', 'f96_display': 'Oui', 'f96_structured': bytearray(b'N.'), 'f176_display': None}
  formdef = <FormDef 'Cr\xc3\xa9ation de votre profil famille' id:24>
  self = <Creation-De-Votre-Profil-Famille id:25>
  value = ''
  field = <wcs.fields.DateField object at 0x3e1c4d0>
  data = {'194_structured': {u'text': u'Alfortville', u'post_code': u'94140', u'id': u'1'}, '195': '152', '194': '1', '193': None, '192': '11', '114': None, '116': '', '110': '', '176': None, '119': None, '48': '1', '96_display': 'Oui', '4': '', '7': '', '105': '', '77': '', '98': '', '123': None, '103': None, '79': '', '96': 'Oui', '11': '', '120': None, '12': '', '19': '', '18': '', '194_display': 'Alfortville', '195_display': 'DE GENEVE', '192_display': 'Rue'}
```

```
File "/usr/lib/python2.7/dist-packages/wcs/sql.py", line 1047, in store
  1045         sql_dict['actions_roles_array'] = [str(x) for x in self.actions_roles if x]
  1046
> 1047         sql_dict.update(self.get_sql_dict_from_data(self.data, self._formdef))
  1048         conn, cur = get_connection_and_cursor()
  1049         if not self.id:

locals:
  x = 'f27d7ce14b4b4f19bf16c7cd5018f8b2'
  self = <Creation-De-Votre-Profil-Famille id:25>
  sql_dict = {'status': 'wf-1', 'concerned_roles_array': ['f27d7ce14b4b4f19bf16c7cd5018f8b2'], 'tracking_code': 'GXFRFZPV', 'workflow_roles_array': None, 'workflow_data': bytearray(b'N.'), 'workflow_roles': None, 'user_id': 2, 'submission_context': None, 'actions_roles_array': [], 'receipt_time': (datetime.datetime(2015, 11, 4, 21, 35, 30)), 'user_hash': None, 'id_display': None, 'back_office_submission': False, 'page_no': '4', 'anonymised': None}
```

```
File "/usr/lib/python2.7/dist-packages/wcs/sql.py", line 267, in f
  265         except psycopg2.Error:
  266             get_connection().rollback()
> 267             raise
  268         return f
  269
```

```

locals:
  args = (<Creation-De-Votre-Profil-Famille id:25>,)
  func = <function store at 0x39ce398>
  kwargs = {}

File "/usr/lib/python2.7/dist-packages/wcs/forms/root.py", line 879, in submitted
877         return redirect('%s/' % user_forms[0].id)
878
> 879         filled.store()
880         self.set_tracking_code(filled)
881         session.remove_magictoken(get_request().form.get('magictoken'))

locals:
  existing_formdata = None
  self = <modules.formpage.AlternateFormPage object at 0x3e1cf50>
  session = <BasicSession at 45dad50: f3df20e259925cd0>
  form = <wcs.qommon.form.Form object at 0x3d7c510>
  filled = <Creation-De-Votre-Profil-Famille id:25>

File "/usr/lib/python2.7/dist-packages/wcs/forms/root.py", line 734, in _q_index
732         return template.error_page(_('This form has already been submitted.'))
733
> 734         return self.submitted(form, existing_formdata)
735
736

locals:
  existing_formdata = None
  form = <wcs.qommon.form.Form object at 0x3d7c510>
  log_detail = None
  magictoken = 'bc78ed6b2f760a05'
  step = 2
  session = <BasicSession at 45dad50: f3df20e259925cd0>
  session_magic_token = {'194_structured': {'u'text': u'Alfortville', u'post_code': u'94140', u'
id': u'1'}, '48': '1', '96_display': 'Oui', '194': '1', '194_display': 'Alfortville', '195_display
': 'DE GENEVE', '193': None, '192': '11', '195': '152', '123': None, '192_display': 'Rue', '96': '
Oui', 'draft_formdata_id': 25}
  form_data = {'194_structured': {'u'text': u'Alfortville', u'post_code': u'94140', u'id': u'1'}
, '48': '1', '96_display': 'Oui', '194': '1', '194_display': 'Alfortville', '195_display': 'DE GEN
EVE', '193': None, '192': '11', '195': '152', '123': None, '192_display': 'Rue', '96': 'Oui', 'dra
ft_formdata_id': 25}
  no_magic = <object object at 0x3add4b0>
  editing = None
  self = <modules.formpage.AlternateFormPage object at 0x3e1cf50>

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 67, in _q_traverse
65         raise TraversalError
66         elif hasattr(obj, '__call__'):
> 67             return obj()
68         else:
69             return obj

locals:
  component = ''
  self = <modules.formpage.AlternateFormPage object at 0x3e1cf50>
  obj = <bound method AlternateFormPage._q_index of <modules.formpage.AlternateFormPage object
at 0x3e1cf50>>
  name = '_q_index'
  path = []

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 63, in _q_traverse
61         if path:
62             if hasattr(obj, '_q_traverse'):
> 63                 return obj._q_traverse(path)
64             else:
65                 raise TraversalError

```

```

locals:
  component = 'creation-de-votre-profil-famille'
  self = <modules.root.FormsRootDirectory object at 0x3e1c8d0>
  obj = <modules.formpage.AlternateFormPage object at 0x3e1cf50>
  name = None
  path = ['']

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 91, in _q_traverse
  89     def _q_traverse(self, path):
  90         self._q_access()
>  91         return super(AccessControlled, self)._q_traverse(path)
  92
  93

locals:
  path = ['creation-de-votre-profil-famille', '']
  self = <modules.root.FormsRootDirectory object at 0x3e1c8d0>

File "/usr/lib/pymodules/python2.7/quixote/directory.py", line 63, in _q_traverse
  61         if path:
  62             if hasattr(obj, '_q_traverse'):
>  63                 return obj._q_traverse(path)
  64             else:
  65                 raise TraversalError

locals:
  component = 'famille'
  self = <modules.root.AlternateRootDirectory object at 0x36d5190>
  obj = <modules.root.FormsRootDirectory object at 0x3e1c8d0>
  name = None
  path = ['creation-de-votre-profil-famille', '']

File "/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/modules/root.py", line 845, in _q_traverse
  843         return redirect('%s%s/%s' % (base_url, f.category.url_name, uri_rest))
  844
>  845         raise e
  846
  847

locals:
  path = ['famille', 'creation-de-votre-profil-famille', '']
  self = <modules.root.AlternateRootDirectory object at 0x36d5190>
  response = <qommon.http_response.HTTPResponse instance at 0x4860b90>

File "/usr/lib/pymodules/python2.7/quixote/publish.py", line 253, in try_publish
  251         permanent=True)
  252         components = path[1:].split('/')
>  253         output = self.root_directory._q_traverse(components)
  254         # The callable ran OK, commit any changes to the session
  255         self.finish_successful_request()

locals:
  path = '/famille/creation-de-votre-profil-famille/'
  self = <publisher.WcsPublisher instance at 0x3829f80>
  request = <qommon.http_request.HTTPRequest instance at 0x4860248>
  components = ['famille', 'creation-de-votre-profil-famille', '']

File "/usr/lib/python2.7/dist-packages/wcs/qommon/publisher.py", line 616, in try_publish
  614         for extra_source in self.extra_sources:
  615             self.substitutions.feed(extra_source(self, request))
>  616         return Publisher.try_publish(self, request)
  617
  618     def get_site_language(self):

locals:
  extra_source = <class 'modules.abelium_domino_vars.DominoVariables'>

```

```
pystatsd = <module 'qommon.vendor.pystatsd' from '/usr/lib/python2.7/dist-packages/wcs/qommon
/vendor/pystatsd.pyc'>
request = <qommon.http_request.HTTPRequest instance at 0x4860248>
script_name = ''
prefix = 'm'
override_template_keys = {'m': 'mobile'}
canonical_hostname = 'demarches-alfortville.test.entrouvert.org'
self = <publisher.WcsPublisher instance at 0x3829f80>
```

```
File "/usr/lib/python2.7/dist-packages/wcs/publisher.py", line 215, in try_publish
213         if request.get_header('X_WCS_IFRAME_MODE', '') in ('true', 'yes'):
214             request.response.iframe_mode = True
> 215         return QommonPublisher.try_publish(self, request)
216
217     def initialize_sql(self):
```

locals:

```
self = <publisher.WcsPublisher instance at 0x3829f80>
request = <qommon.http_request.HTTPRequest instance at 0x4860248>
```

```
File "/usr/lib/pymodules/python2.7/quixote/publish.py", line 281, in process_request
279         except:
280             # Some other exception, generate error messages to the logs, etc.
> 281             output = self.finish_failed_request()
282             output = self.filter_output(request, output)
283             self.logger.log_request(request, start_time)
```

locals:

```
start_time = 1446669329.407665
request = <qommon.http_request.HTTPRequest instance at 0x4860248>
self = <publisher.WcsPublisher instance at 0x3829f80>
```

```
File "/usr/lib/python2.7/dist-packages/wcs/qommon/publisher.py", line 920, in process
918     def process(self, stdin, env):
919         request = HTTPRequest(stdin, env)
> 920         self.response = self.process_request(request)
921         return self.response
922
```

locals:

```
self = <publisher.WcsPublisher instance at 0x3829f80>
stdin = <open file '<socket>', mode 'r' at 0x3c350c0>
request = <qommon.http_request.HTTPRequest instance at 0x4860248>
env = {'HTTP_X_AU_QUOTIDIEN_LOCKED': 'False', 'HTTP_REFERER': 'https://demarches-alfortville.
test.entrouvert.org/famille/creation-de-votre-profil-famille/', 'SERVER_SOFTWARE': 'Apache/2.2.22
(Debian)', 'SCRIPT_NAME': '', 'REQUEST_METHOD': 'POST', 'PATH_INFO': '/famille/creation-de-votre-p
rofil-famille/', 'SERVER_PROTOCOL': 'HTTP/1.1', 'QUERY_STRING': '', 'SSL_TLS_SNI': 'demarches-alfor
tville.test.entrouvert.org', 'CONTENT_LENGTH': '4126', 'HTTP_USER_AGENT': 'Mozilla/5.0 (X11; Linu
x x86_64; rv:42.0) Gecko/20100101 Firefox/42.0 Icedove/42.0', 'HTTP_CONNECTION': 'keep-alive', '
HTTP_COOKIE': 'publik_portal_agent_url=https%3A%2F%2Fportail-agent-alfortville.test.entrouvert.org
%2F; publik_portal_agent_title=Portail%20agent; wcs-7eafd8="d11a1783ed5aa07f"; wcs-f6f14f="f3df20e
259925cd0"; A2_OPENED_SESSION=1', 'SERVER_NAME': 'demarches-alfortville.test.entrouvert.org', 'REM
OTE_ADDR': '109.190.108.22', 'SERVER_PORT': '443', 'SERVER_ADDR': '94.23.114.98', 'DOCUMENT_ROOT':
'/usr/share/wcs/w
eb/', 'SCGI': '1', 'SERVER_ADMIN': 'webmaster@entrouvert.org', 'SCRIPT_URI': 'https://demarches-a
lfortville.test.entrouvert.org/famille/creation-de-votre-profil-famille/', 'REMOTE_USER': '2', 'HT
TP_HOST': 'demarches-alfortville.test.entrouvert.org', 'SCRIPT_URL': '/famille/creation-de-votre-p
rofil-famille/', 'HTTPS': 'on', 'HTTP_CONTENT_TYPE': 'multipart/form-data; boundary=-----
-----18969569447406159851420424905', 'HTTP_CONTENT_LENGTH': '4126', 'REQUEST_URI': '/famil
le/creation-de-votre-profil-famille/', 'HTTP_ACCEPT': 'text/html,application/xhtml+xml,application
/xml;q=0.9,*/*;q=0.8', 'REMOTE_PORT': '62371', 'HTTP_ACCEPT_LANGUAGE': 'fr,fr-FR;q=0.8,en-US;q=0.5
,en;q=0.3', 'CONTENT_TYPE': 'multipart/form-data; boundary=-----189695694474
06159851420424905', 'HTTP_ACCEPT_ENCODING': 'gzip, deflate'}
```

```
File "/usr/lib/pymodules/python2.7/quixote/server/scgi_server.py", line 27, in handle_connection
25         env['PATH_INFO'] = path[len(prefix):] + env.get('PATH_INFO', '')
26
```

```

> 27         response = self.publisher.process(input, env)
28         try:
29             response.write(output)

locals:
  output = <open file '<socket>', mode 'w' at 0x3c35540>
  self = <qommon.scgi_server.QommonHandler instance at 0x36d42d8>
  conn = <socket object, fd=20, family=2, type=1, protocol=0>
  env = {'HTTP_X_AU_QUOTIDIEN_LOCKED': 'False', 'HTTP_REFERER': 'https://demarches-alfortville.
test.entrouvert.org/famille/creation-de-votre-profil-famille/', 'SERVER_SOFTWARE': 'Apache/2.2.22
(Debian)', 'SCRIPT_NAME': '', 'REQUEST_METHOD': 'POST', 'PATH_INFO': '/famille/creation-de-votre-p
rofil-famille/', 'SERVER_PROTOCOL': 'HTTP/1.1', 'QUERY_STRING': '', 'SSL_TLS_SNI': 'demarches-alf
ortville.test.entrouvert.org', 'CONTENT_LENGTH': '4126', 'HTTP_USER_AGENT': 'Mozilla/5.0 (X11; Linu
x x86_64; rv:42.0) Gecko/20100101 Firefox/42.0 Icedove/42.0', 'HTTP_CONNECTION': 'keep-alive', '
HTTP_COOKIE': 'publik_portal_agent_url=https%3A%2F%2Fportail-agent-alfortville.test.entrouvert.org
%2F; publik_portal_agent_title=Portail%20agent; wcs-7eafd8="d11a1783ed5aa07f"; wcs-f6f14f="f3df20e
259925cd0"; A2_OPENED_SESSION=1', 'SERVER_NAME': 'demarches-alfortville.test.entrouvert.org', 'REM
OTE_ADDR': '109.190.108.22', 'SERVER_PORT': '443', 'SERVER_ADDR': '94.23.114.98', 'DOCUMENT_ROOT':
'/usr/share/wcs/w
eb/', 'SCGI': '1', 'SERVER_ADMIN': 'webmaster@entrouvert.org', 'SCRIPT_URI': 'https://demarches-a
lfortville.test.entrouvert.org/famille/creation-de-votre-profil-famille/', 'REMOTE_USER': '2', 'HT
TP_HOST': 'demarches-alfortville.test.entrouvert.org', 'SCRIPT_URL': '/famille/creation-de-votre-p
rofil-famille/', 'HTTPS': 'on', 'HTTP_CONTENT_TYPE': 'multipart/form-data; boundary=-----
-----18969569447406159851420424905', 'HTTP_CONTENT_LENGTH': '4126', 'REQUEST_URI': '/famil
le/creation-de-votre-profil-famille/', 'HTTP_ACCEPT': 'text/html,application/xhtml+xml,application
/xml;q=0.9,*/*;q=0.8', 'REMOTE_PORT': '62371', 'HTTP_ACCEPT_LANGUAGE': 'fr,fr-FR;q=0.8,en-US;q=0.5
,en;q=0.3', 'CONTENT_TYPE': 'multipart/form-data; boundary=-----189695694474
06159851420424905', 'HTTP_ACCEPT_ENCODING': 'gzip, deflate'}
  input = <open file '<socket>', mode 'r' at 0x3c350c0>

File "/usr/lib/python2.7/dist-packages/wcs/qommon/scgi_server.py", line 35, in handle_connection
33     def handle_connection(self, conn):
34         self.number_of_connection_handled = self.number_of_connection_handled + 1
> 35         quixote.server.scgi_server.QuixoteHandler.handle_connection(self, conn)
36         # input, output and conn are closed, long running jobs could be done
37         # here.

locals:
  self = <qommon.scgi_server.QommonHandler instance at 0x36d42d8>
  conn = <socket object, fd=20, family=2, type=1, protocol=0>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 71, in serve
69         conn.setblocking(1)
70         os.close(fd)
> 71         self.handle_connection(conn)
72
73

locals:
  self = <qommon.scgi_server.QommonHandler instance at 0x36d42d8>
  fd = 19
  conn = <socket object, fd=20, family=2, type=1, protocol=0>

File "/usr/lib/pymodules/python2.7/scgi/scgi_server.py", line 194, in spawn_child
192             # the connection in the child
193             os.close(child_fd)
> 194             self.handler_class(parent_fd).serve()
195             sys.exit(0)
196         else:

locals:
  self = <qommon.scgi_server.SCGIServer instance at 0x36d40e0>
  pid = 0
  flags = 2
  child_fd = 19
  parent_fd = 18
  conn = None

```

```

File "/usr/lib/pymodules/python2.7/cgi/scgi_server.py", line 172, in __init__
 170         self.max_children = max_children
 171         self.children = {} # { pid : fd }
> 172         self.spawn_child()
 173         self.restart = 0
 174

locals:
  max_children = 5
  host = 'localhost'
  handler_class = <function create_handler at 0x37c2488>
  port = 3001
  self = <qommon.scgi_server.SCGIServer instance at 0x36d40e0>

File "/usr/lib/python2.7/dist-packages/wcs/qommon/scgi_server.py", line 73, in run
 71
 72     s = SCGIServer(create_handler, host=host, port=port,
> 73                       max_children=max_children)
 74     s.serve()
 75

locals:
  create_handler = <function create_handler at 0x37c2488>
  handler_connection_limit = -1
  max_children = 5
  create_publisher = <bound method classobj.create_publisher of <class publisher.WcsPublisher a
t 0x2defae0>>
  script_name = None
  host = 'localhost'
  spawn_cron = True
  port = 3001

File "/usr/lib/python2.7/dist-packages/wcs/ctl/start.py", line 138, in execute
 136
 137     try:
> 138         run_function(publisher.WcsPublisher.create_publisher, **run_kwargs)
 139         except socket.error, e:
 140             self.del_pid()

locals:
  publisher = <module 'publisher' from '/usr/lib/python2.7/dist-packages/wcs/publisher.pyc'>
  base_app_dir = '/var/lib/wcs-au-quotidien'
  args = []
  tenant_path = '/var/lib/wcs-au-quotidien/jerome.au-quotidien.com'
  self = <wcs.ctl.start.CmdStart object at 0x270f410>
  hostname = 'jerome.au-quotidien.com'
  pub = <publisher.WcsPublisher instance at 0x37c15f0>
  sub_options = <Values at 0x272fa28: {'http': False, 'silent': False, 'app_dir': None, 'extra'
: ['/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/'], 'max_children': None, 'handler_connect
ion_limit': None, 'script_name': None, 'daemonize': False, 'data_dir': None, 'port': 3001, 'pidfil
e': None}>
  run_function = <function run at 0x2731f50>
  base_options = <Values at 0x26fde60: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>
  run_kwargs = {'port': 3001, 'spawn_cron': True}

File "/usr/lib/python2.7/dist-packages/wcs/qommon/ctl.py", line 69, in run
 67         for i, extra in enumerate(sub_options.extra):
 68             self.config.set("extra", "cmd_line_extra_%d" % i, extra)
> 69         return self.execute(base_options, sub_options, args)
 70
 71     def parse_args(self, args):

locals:
  extra = '/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/'
  i = 0
  self = <wcs.ctl.start.CmdStart object at 0x270f410>

```

```
args = []
sub_options = <Values at 0x272fa28: {'http': False, 'silent': False, 'app_dir': None, 'extra'
: ['/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/'], 'max_children': None, 'handler_connect
ion_limit': None, 'script_name': None, 'daemonize': False, 'data_dir': None, 'port': 3001, 'pidfil
e': None}>
base_options = <Values at 0x26fde60: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>
```

```
File "/usr/lib/python2.7/dist-packages/wcs/qommon/ctl.py", line 159, in run
157     command_class = self.get_commands()[command]
158     cmd = command_class()
> 159     return cmd.run(args, options)
160
```

locals:

```
cmd = <wcs.ctl.start.CmdStart object at 0x270f410>
args = ['--extra', '/usr/lib/pymodules/python2.7/extra-wcs-au-quotidien/']
self = <wcs.qommon.ctl.Ctl object at 0x2413110>
command_class = <class 'wcs.ctl.start.CmdStart'>
command = 'start'
cmd_prefix = 'wcs.ctl'
options = <Values at 0x26fde60: {'configfile': '/etc/wcs/wcs-au-quotidien.cfg'}>
```

```
File "/usr/sbin/wcsctl", line 8, in <module>
6
7 ctl = wcs.qommon.ctl.Ctl(cmd_prefixes=['wcs.ctl'])
> 8 ctl.run(sys.argv[1:])
9
```

locals:

```
wcs = <module 'wcs' from '/usr/lib/python2.7/dist-packages/wcs/__init__.pyc'>
__builtins__ = <module '__builtin__' (built-in)>
__file__ = '/usr/sbin/wcsctl'
__package__ = None
sys = <module 'sys' (built-in)>
ctl = <wcs.qommon.ctl.Ctl object at 0x2413110>
__name__ = '__main__'
__doc__ = None
```

Form:

```
_form_id      '6dbdbbd3e7bb7507'
f103          ''
f103_label    ''
f105          ''
f11           ''
f110         ''
f114         ''
f114_label    ''
f116         ''
f119$token    ''
f12          ''
f120$token    ''
f123$token    ''
f176         ''
f176_label    ''
f18          ''
f19          ''
f192         '11'
f192_label    'Rue'
f193         ''
f193_label    ''
f194         '1'
f194_label    'Alfortville'
f195         '152'
f195_label    'DE GENEVE'
f4           ''
f48          '1'
f7           ''
```

```
f77          ''
f79          ''
f96          'Oui'
f96_label    'Oui'
f98          ''
magictoken   'bc78ed6b2f760a05'
step         '2'
submit       'Valider'

Cookies:
A2_OPENED_SESSION '1'
publik_portal_agent_title 'Portail%20agent'
publik_portal_agent_url 'https%3A%2F%2Fportail-agent-alfortville.test.entrouvert.org%2F'
wcs-7eafd8     'd11a1783ed5aa07f'
wcs-f6f14f     'f3df20e259925cd0'

Environment:
CONTENT_LENGTH '4126'
CONTENT_TYPE   'multipart/form-data; boundary=-----18969569447406159851420424905'
DOCUMENT_ROOT '/usr/share/wcs/web/'
HTTPS          'on'
HTTP_ACCEPT    'text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8'
HTTP_ACCEPT_ENCODING 'gzip, deflate'
HTTP_ACCEPT_LANGUAGE 'fr,fr-FR;q=0.8,en-US;q=0.5,en;q=0.3'
HTTP_CONNECTION 'keep-alive'
HTTP_CONTENT_LENGTH '4126'
HTTP_CONTENT_TYPE 'multipart/form-data; boundary=-----18969569447406159851420424905'
HTTP_COOKIE    'publik_portal_agent_url=https%3A%2F%2Fportail-agent-alfortville.test.entrouvert.org%2F; publik_portal_agent_title=Portail%20agent; wcs-7eafd8="d11a1783ed5aa07f"; wcs-f6f14f="f3df20e259925cd0"; A2_OPENED_SESSION=1'
HTTP_HOST      'demarches-alfortville.test.entrouvert.org'
HTTP_REFERER   'https://demarches-alfortville.test.entrouvert.org/famille/creation-de-votre-profil-famille/'
HTTP_USER_AGENT 'Mozilla/5.0 (X11; Linux x86_64; rv:42.0) Gecko/20100101 Firefox/42.0 Iceweasel/42.0'
HTTP_X_AU_QUOTIDIEN_LOCKED 'False'
PATH_INFO      '/famille/creation-de-votre-profil-famille/'
QUERY_STRING   ''
REMOTE_ADDR    '109.190.108.22'
REMOTE_PORT    '62371'
REMOTE_USER    '2'
REQUEST_METHOD 'POST'
REQUEST_URI    '/famille/creation-de-votre-profil-famille/'
SCRIPT_NAME    ''
SCRIPT_URI     'https://demarches-alfortville.test.entrouvert.org/famille/creation-de-votre-profil-famille/'
SCRIPT_URL     '/famille/creation-de-votre-profil-famille/'
SERVER_ADDR    '94.23.114.98'
SERVER_ADMIN   'webmaster@entrouvert.org'
SERVER_NAME    'demarches-alfortville.test.entrouvert.org'
SERVER_PORT    '443'
SERVER_PROTOCOL 'HTTP/1.1'
SERVER_SOFTWARE 'Apache/2.2.22 (Debian)'
SSL_TLS_SNI    'demarches-alfortville.test.entrouvert.org'
```

## Historique

### #1 - 04 novembre 2015 21:50 - Thomas Noël

Reproduit 3 fois de suite sur la machine de Brice (à mes côtés). Pas reproduit chez moi.

### #2 - 05 novembre 2015 00:08 - Frédéric Péters

- Fichier 0001-form-fix-handling-of-optional-date-fields-8867.patch ajouté

- Statut changé de Nouveau à En cours



- Patch proposed changé de Non à Oui

Je reproduis avec le test joint (en SQL); correction également attachée.

### #3 - 05 novembre 2015 00:36 - Frédéric Péters

Je viens de placer le patch ainsi sur auquo-test et alfortville.dev.

### #4 - 05 novembre 2015 01:37 - Thomas Noël

Je ne suis pas sûr de voir le rapport exact du patch avec le titre du ticket, car les champs dates sont tous obligatoires dans notre formulaire. Le problème c'est surtout que quasi **tous** les champs de la demande sont à None à la fin (alors que tous correctement saisis avant). J'ai vu la chose se passer 3 fois de suite lors de tests avec Brice, mais impossible à reproduire chez moi. J'ai juste eu le cas en fin d'après-midi, une seule fois. Sur wcs 1.20 toujours.

Ceci étant, effectivement, la trace finale ne montre que la conséquence, et pas la cause du soucis...

(Bon, ceci dit, ça a sans doute permis de voir un bogue ailleurs, à savoir crash sur champs date optionnels vides, oui).

### #5 - 05 novembre 2015 09:09 - Frédéric Péters

Moi je ne voyais pas de rapport entre le titre et la trace donnée...

### #6 - 05 novembre 2015 10:21 - Thomas Noël

J'aurais dû dire que dans la trace, le truc anormal est

```
data = {'194_structured': {'u'text': u'Alfortville', u'post_code': u'94140', u'id': u'1'}, '195': '152', '194': '1', '193': None, '192': '11', '114': None, '116': '', '110': '', '176': None, '119': None, '48': '1', '96_display': 'Oui', '4': '', '7': '', '105': '', '77': '', '98': '', '123': None, '103': None, '79': '', '96': 'Oui', '11': '', '120': None, '12': '', '19': '', '18': '', '194_display': 'Alfortville', '195_display': 'DE GENEVE', '192_display': 'Rue'}
```

### #7 - 05 novembre 2015 20:51 - Frédéric Péters

- Version cible v1.21 supprimé

### #8 - 06 novembre 2015 11:11 - Frédéric Péters

- Patch proposed changé de Oui à Non

### #9 - 12 février 2016 15:19 - Thomas Noël

- Statut changé de En cours à Fermé

était un problème d'autosave

## Fichiers

0001-form-fix-handling-of-optional-date-fields-8867.patch

2,62 ko 04 novembre 2015

Frédéric Péters